


Overview



### Introduction

The highly available HP StorageWorks SAN Switch 2/8V and 2/8V Power Pack offer 2 Gb connectivity for an entry-level storage area network (SAN), and the ability to grow to a core-to-edge infrastructure. The simplicity and ease-of-use advantages of the SAN Switch 2/8V and 2/8V Power Pack can help increase administrator productivity and lower the cost of management. This can be especially beneficial for organizations with limited IT expertise.

The Switch delivers eight high performance Auto Sensing 1 and 2 Gb Fibre Channel ports. In addition, the SAN Switch 2/8V and 2/8V Power Pack are fully non-blocking and provide 16 Gb switching (2 Gb full duplex) capacity for un-congested sustained, 2 Gb full duplex throughput. The SAN Switch 2/8V scales to a maximum fabric configuration of two switches and can be upgraded to full SAN configurations by purchasing a full fabric upgrade license. Small-form-factor-pluggable optical transceivers (SFPs) must be ordered separately.

The Power Pack provides the SAN administrator with the necessary tools to monitor the health and performance of the network, while also ensuring the highest levels of security, scalability and manageability. Available pre-configured on the switch or as an upgrade, Power Pack also provides the foundation for integration into HP OpenView Storage Area Manager (SAM), enabling infrastructure management through a single-pane-of-glass. The Power Pack tools can be ordered separately, as well.

### Key Features and Benefits

- Reduced Total Cost of Ownership for SAN Infrastructure
  - O Enables storage consolidation, simplified management of data center SAN environment
- Interoperability with the more than 1 MILLION port HP SAN Switch installed base
- Highest integration with HP Open View Storage Area Manager via:
  - SAN Switch API
  - O SAN Switch element managers
  - HP StorageWorks Fabric Manager
- Broadest range of compatibility with SAN products
  - O Multi-vendor server and storage environment
    - O Widest range of HP SAN solutions
    - O Backward compatible with previously installed 1Gb SAN Switches
- HP Power Pack (Optional) highest supported modular functionality
  - O Trunking highest throughput between switches (8Gb/sec)
  - HW enforced WWN Zoning (Advanced Zoning)
  - O Proactive threshold monitor (Fabric Watch)
  - O Advanced Performance Monitor
  - O Per Switch element manager (WebTools)
  - O Support for extended distance (Extended Fabrics)
  - O Support for multi-protocol gateways (Remote Switch)
- Broadest Range of HP Packaged SAN Services
  - O Mission critical SAN Services SAN-ES
  - O Assessment and installation services for security
- Flexible storage connectivity
  - O The only SAN solutions providing the complete HP SAN Switch functionality from Embedded to Enterprise. The HP SAN Switch value line products allows the capability to apply the complete SAN Switch functionality to an affordable entry level SAN deployment and then to grow that deployment to the largest SAN fabric solutions supported by HP.



# HP StorageWorks SAN Switch 2/8V and 2/8V Power Pack B-Series Family

# **QuickSpecs**

Models

HP StorageWorks SAN	HP StorageWorks SAN Switch 2/8V	AA979A
Switch 2/8V SAN Switch	HP StorageWorks SAN Switch 2/8V 2-Switch to Full Fabric Upgrade License	AA975A
2/8V Power Pack Models	HP StorageWorks SAN Switch 2/8V Power Pack	AA980A
	SAN Switch Power Pack Software Bundle (optional)	T3573A



### Product Highlights

8 non-blocking ports

Eight auto-sensing 1 and 2 Gb universal, self-configuring ports (F, FL, E). Can be programmed to fixed 1 Gb or 2 Gb

speed. Full 16 Gb switching capacity for un-congested fully sustained, 2 Gb full duplex throughput.

Configuration support

SAN Switch 2/8V Power Pack will interoperate with 1Gb and 2Gb B-Series SAN Switches running the firmware version defined in the SAN Design Guide http://h18000.www1.hp.com/products/storageworks/san/documentation.html

High-availability features

Hot Code Load Activation

Advanced Fabric Services

- ISL Trunking (optional)
- Hardware Enforced Zoning
- WebTools
- Remote Switch (optional)
- Fabric Watch (optional)
- End-to-End Performance Analysis (optional)

Manageability

- WebTools
- OpenView
- API
- IP
- SNMP

Scalability

- SAN Switch 2/8V has a two switch SAN scaling limit (standard)
- Optional full SAN scaling license

## Software Components, Standard

Frame Filtering

An ASIC based capability in the 2Gb family of switches that enables new applications and features. The switch now has the ability to "view" the first 64 bytes of the Fibre Channel frame. At this time, Frame Filtering enables advanced capabilities such as Advanced Zoning and Advanced Performance Monitoring.

Advanced Zoning

In the 2 Gb generation of switches, WWN Zoning and Access Control are enforced by hardware that provides the same simple administration previously enforced only with software. Administrators can organize a physical fabric into logical groups and prevent unauthorized access by devices outside the Zone.

WebTools

Enables organizations to monitor and manage single Fibre Channel switches and small SAN fabrics. Tasks can be performed through a Java-capable Web browser from a standard laptop, desktop PC or workstation from any location within the enterprise.

## Software Components, Optional

SAN Switch 2/8V Power Pack Software Bundle Includes bundled license for:

- ISL Trunking
- Advanced Performance Monitoring
- Fabric Watch
- Extended Fabric
- Remote Switch



## Product Highlights

	JN	

For high performance enhanced Trunking, this optional license logically groups up to four E-ports to provide a high bandwidth trunk between two switches. Each 2 Gb switch needs its own license. The switch operating system views the trunk as a single, high bandwidth resource (up to 8 Gb) when routing connections between switches. Connections are load-balanced across the individual links, which comprise the logical trunk group. Each 8-port switch can have a total of two separate 4-port Trunk groups.

### Advanced Performance Monitor

This enabling technology helps administrators monitor and watch specific fabric metrics from a SID (Source ID) to a DID (Destination ID), so they can fine-tune and scale the fabric more efficiently. Plus, Advanced Performance Monitoring includes the ability for early warning detection of hot spots within the fabric, a powerful tool for maintaining overall balanced performance.

### Fabric Watch

Fabric Watch enables each switch to monitor the SAN for potential faults-and automatically alert network managers to problems before they become failures. Fabric Watch tracks a variety of SAN fabric elements, events, and counters. Monitoring fabric-wide events, ports, SFPs, and environmental parameters permits early fault detection and isolation as well as performance measurement. Each switch in the SAN needs its own Fabric Watch license.

#### **Extended Fabric**

Extends all of the scalability, reliability, and performance benefits of Fibre Channel Storage Area Networks (SANs) beyond the native 10 km distance specified by the Fibre Channel standard. Required with future use of Very Long Distance SFPs and/or wavelength division multiplexing (WDM or DWDM).

### Remote Switch

Remote switch fabric functions with the aid of a bridging device or network bridge. The network bridge supports both Fibre Channel physical interfaces, as well as secondary non-Fibre Channel FCIP physical interface.

### Fabric Manager (v4.1.1)

Fabric Manager is a highly scalable, Java-based application that manages multiple switches and multiple fabrics (up to eight) in real time, helping SAN administrators with SAN configuration, monitoring, dynamic provisioning, and daily management. SAN administrators gain rapid access to critical SAN information across multiple personality fabrics.

### Secure Fabric OS

Secure Fabric OS™ is a comprehensive security solution for SAN fabrics, providing policy-based security protection for more predictable change management, assured configuration integrity and reduced risk of downtime. Secure Fabric OS protects the network by using the strongest, enterprise-class security methods available, including digital certificates and digital signatures, multiple levels of password protection, strong password encryption and Public Key Infrastructure (PKI)-based authentication, and 128-bit encryption of the switch's private key used for digital signatures. With its flexible design, Secure Fabric OS enables organizations to customize SAN security to meet specific policy requirements. In addition, Secure Fabric OS works in conjunction with Advanced Zoning to further secure access to the SAN, simplify storage management, and reduce provisioning time.

## Full Fabric License for 2/8V

Expands connectivity from 2 switch scaling to full fabric scaling. Please see the following web site for further information: http://h18006.www1.hp.com/products/storageworks/san/documentation.html



### HP StorageWorks SAN Switch 2/8V and 2/8V Power Pack B-Series Family

## **QuickSpecs**

## Service and Support, HP Care Pack and Warranty Information

#### Warranty

(1-1-1) Hardware Warranty - One-year on-site warranty, 8x5, next business day response, installation not included. NOTE: The hardware warranty covers firmware and embedded non-saleable software. Saleable software carries its own warranty, see below.

Software Warranty - HP warrants only that the software media will be free of physical defects for a period of ninety (90) days from delivery. EXCLUSIVE REMEDY. The entire liability of HP and its suppliers and your exclusive remedy for software that does not conform to this Limited Warranty shall be the repair or replacement of the defective media. This warranty and remedy are subject to your returning the defective media during the warranty period to HP in the country in which you obtained the software.

### **HP Service & Warranty** Support

HP Service & Warranty Support Additional Warranty protection and/or HP Installation packages can be purchased. NOTE: Certain restrictions and exclusions apply. Consult the Customer Support Center for details. HP provides a one-year, hardware limited warranty, fully supported by a worldwide network of resellers and service providers.

In addition, available service offerings include a full range of HP Care Pack packaged hardware and software services:

- Extended coverage hours and enhanced response times
- System management and performance services

For more information on warranty and support options, please visit our Web site at: http://www.hp.com/hps/tech/storage/supp/.

#### Software Product Services

- Stand-alone telephone support
- Rights to new license version
- Media and documentation updates

### Hardware Product Services

- Installation services
- On-site maintenance (includes warranty support)
- Response time upgrades during the warranty period
- Post-warranty coverage

### **HP Care Pack Services** Warranty Upgrade Options

Service offerings include a full range of Customer HP Care Pack services for both hardware and software services:

- Response Upgrade on-site response from next business day to same day 4-hours
- Coverage Extend hours of coverage from 5 days x 9 hours to 7 days x 24 hours
- Duration Select duration of coverage for a period of 1, 3, or 5 years

Additional Warranty protection and/or HP Installation packages can be purchased.

NOTE: Certain restrictions and exclusions apply. Consult the HP Customer Support Center for details.

HP Care Pack Information HP Care Pack is defined as an upgrade to the product warranty attribute, available for a specific duration and hours of coverage

- HP Care Pack is not available for less than the product's warranty duration.
- HP Care Pack is available for sale anytime during the warranty period for most products, but the commencement date will be the same as the Warranty Start Date (delivery date to end user customer). Proof of purchase may be required.
- HP Care Pack services are prepaid.

For additional HP Care Pack (hardware & software) information, as well as orderable part numbers, please refer to the URL

http://h18005.www1.hp.com/services/carepag/index.html

### Additional Services

Implementation service, SAN Architecture service. For more information on service options, please visit our Web site at: http://www.hp.com/go/san.



## Family Information

Features	MSA SAN Switch 2/8	SAN Switch 2/8V and SAN	SAN Switch 2/16V	SAN Switch 2/16N FF and	SAN Switch 2/32 and SAN	Core 2/64 and Core 2/64	SAN Director 2/128 and
	(embedded	Switch 2/8V		SAN Switch	Switch 2/32	Power Pack	Director 2/128
	switch)	Power Pack		2/16N Power	Power Pack		Power Pack
				Pack			
Targeted	Workgroups,	Workgroups,	Workgroups,	Departments,	Departments,	Data Centers	Data Centers
Environment	Departments	Departments	Departments	Data Centers	Data Centers		
Port Bandwidth	2 Gbit/sec	2 Gbit/sec	2 Gbit/sec	2 Gbit/sec	2 Gbit/sec	2 Gbit/sec	2 Gbit/sec
Aggregate	32 Gbit/sec	32 Gbit/sec	64 Gbit/sec	64 Gbit/sec	128 Gbit/sec	256 Gbit/sec	512 Gbit/sec
device	end-to-end	end-to-end	end-to-end	end-to-end	end-to-end	end-to-end	end-to-end
bandwith							
OS Support				SAN Design Guide	•		
			ww.compaq.com/pr		T .		
Storage system	MSA 1000	MA8000	MA8000	MA8000	MA8000	MA8000	MA8000
support		EMA12000/	EMA12000/	EMA12000/	EMA12000/	EMA12000/	EMA12000/
		EMA16000 EVA	EMA16000 EVA	EMA16000 EVA	EMA16000 EVA	EMA16000 EVA	EMA16000 EVA
		v2.0, XP, VA	v2.0, XP, VA	v2.0, XP, VA	v2.0, XP, VA	√2.0, XP, VA	∨2.0, XP, VA
Ports	7 external/1	8 SFP	16 SFP	16 SFP	32 SFP	32 SFP Base	32 SFP Base
	internal					64 Total	128 Total
Cascading	Yes	Yes	Yes	Yes	Yes	Yes	Yes
support							
Advanced	Optional Upgrade		Optional Upgrade		Included with	Included with	Included with
Trunking		Power Pack or		Power Pack or	Power Pack or	Power Pack or	Power Pack or
		Optional Upgrade				Optional Upgrade	
Form factor	Embedded	1U	1U	1U	1.5U	14U	14U
Zoning Software	Yes (Included)	Yes (Included)	Yes (Included)	Yes (Included)	Yes (Included)	Yes (Included)	Yes (Included)
Hot plug,	No	No	No	No	Yes	Yes	Yes
redundant							
power supplies							
Hot plug fans	No	No	No	No	Yes	Yes	Yes
Enterprise	Yes	Yes	Yes	Yes	Yes	Yes	Yes
Backup							
Solution (EBS)							
support**							
**NOTE: Require:	s correct Host Bus A	dapter. Not all Ope	rating Systems Suppo	orted.			



## Configuration Information

## Step 1 – Base Configuration

_			
Se	lect	one:	

Model Name	Model Description	Part Number
StorageWorks SAN Switch 2/8V	8-port Fibre Channel Fabric Switch, licenses, docs, and rack rails.	AA979A
	NOTE- Paguiros antical transcaivars listed below	

Fabric Watch, ISL Trunking, Extended Fabric, Remote Switch, Advanced Performance Monitoring

**NOTE:** Requires optical transceivers listed below.

StorageWorks SAN Switch 2/8 8-port Fibre Channel Fabric Switch with bundled software and rack rails.

Fabric Manager Upgrade License (v3.x to v4.1)

Power Pack NOTE: Requires optical transceivers listed below.

Power Pack Software Bundle for SAN Switch

2/8V

2/01		
Optional Software:	Fabric Watch	324504-B21
	ISL Trunking	324506-B21
	Advanced Performance Monitor	324507-B21
	Remote Switch	325891-B21
	Extended Fabric	324505-B21
	Secure Fabric OS for 8 & 16 port switches (v3.x firmware or higher)	332924-B21
	Fabric Manager v4.1.1	345690-B21

### Step 2 – Additional Options

**Optical Transceivers** Short Wave 221470-B21

Short Wave	300834-B21
Long Wave (10 km)	300835-B21
Long Wave (35 km)	300836-B21

2 Gb optical cables LC-LC for between two 2 Gb devices

2 m LC-LC Multi-Mode Fibre Channel Cable	221692-B21
5 m LC-LC Multi-Mode Fibre Channel Cable	221692-B22
15 m LC-LC Multi-Mode Fibre Channel Cable	221692-B23
30 m LC-LC Multi-Mode Fibre Channel Cable	221692-B26
50 m LC-LC Multi-Mode Fibre Channel Cable	221692-B27
LC-SC for between a 1 Gb and a 2 Gb device	
2 m LC-SC Multi-Mode Fibre Channel Cable	221691-B21
5 m LC-SC Multi-Mode Fibre Channel Cable	221691-B22
15 m LC-SC Multi-Mode Fibre Channel Cable	221691-B23
30 m LC-SC Multi-Mode Fibre Channel Cable	221691-B26
50 m LC-SC Multi-Mode Fibre Channel Cable	221691-B27

Fibre Channel Standards FC-AL Rev. 4.5 FC-GS-2 Rev 5.3 FC-PH Rev 4.3 FC-PLDA Rev 2.1 FC-VI Rev 1.5 And Revisions FC-AL-2 Rev 7.0 FC-FG Rev 3.5 FC-PH-2 Rev 7.4 FC-SW Rev 3.3 IPFC RFC 2625

> FC-FLA Rev 2.7 FC-FH Rev 1.7 FC-PH-3 Rev 9.4



AA980A

T3573A

345691-B21

### Technical Specifications

Fibre Channel ports 8 universal ports

Scalability Full fabric architecture:

http://h18006.www1.hp.com/products/storageworks/san/documentation.html

Certified maximum Refer to SAN Design Guide:

http://h18006.www1.hp.com/products/storageworks/san/documentation.html

Interoperability SAN Switch 8, SAN Switch 16, SAN Switch 8-EL, SAN Switch 16-EL, Integrated /32, Integrated /64, SAN Switch2/16, SAN

Switch 2/16-EL, SAN Switch 2/16N, SAN Switch 2/16V, SAN Switch 2/32, Core Switch 2/64, SAN Director 2/128

**Performance** 2.125 Gbit/sec line speed, full duplex

Switch core Non-blocking

**Fabric latency**  $<2 \mu$  sec. with no contention, cut-through routing

Maximum frame size 2112-byte payload

Classes of service Class 2, Class 3, Class F (inter-switch frames)

Port types FL\_Port, F\_Port, and E\_Port; self-discovery based on switch type (U\_Port)

Data traffic types Fabric switches support unicast, multicast (256 groups), and broadcast

Media types Small Form-Factor Pluggable (SFP)

Laser Short-wave up to 1,640 ft (300 m); long-wave up to 6.2 mi (10 km) when available

Fabric services Simple Name Server, Registered State Change Notification (RSN), Alias Server (multicast); and Zoning, WebTools. Optional

Fabric Watch, Extended Fabrics, and Remote Switch

Options SFP media

Supported software Telnet, SNMP, WebTools, Advanced Zoning, Fabric Watch, Extended Fabrics, Remote Switch

Management access 10/100 Ethernet (RJ-45), serial port

**Diagnostics** POST and embedded online/offline diagnostics

Back-to-front airflow,

power from rear

1 υ, 19-in.–EIA compliant

**Dimensions** Width 10.4 in/26.4 cm

 Height
 1.71 in/4.2 cm

 Depth
 16.9 in/42.8 cm

 Weight
 8.5 lb/3.9 kg

**Environment** Temperature Operating  $50^{\circ}$  to  $104^{\circ}$  F ( $10^{\circ}$  to  $40^{\circ}$  C)

Non-operating -13° to 158° F (-25° to 70° C)

Humidity Operating 5% to 85%

Non-operating  $104^{\circ} \text{ F } (40^{\circ} \text{ C})$ 

Altitude Up to 9,800 ft (3,000 m)

Shock 80 G, 2.5 ms, half sine

Vibration Operating .5 G, 5-500-5 Hz

Non-operating 10 G, 0-5 kHz

Power Supported power range Nominal 100 to 240 VAC contiguous, 0.5 A for each power supply

Operational 90 to 264 VAC

Frequency 47 to 63 Hz

© Copyright 2004 Hewlett-Packard Development Company, L.P.

The information contained herein is subject to change without notice.

The only warranties for HP products and services are set forth in the express warranty statements accompanying such products and services. Nothing herein should be construed as constituting an additional warranty. HP shall not be liable for technical or editorial errors or omissions contained herein.

